

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 452
IDENTITY: DOOM

Revision Date: 01/23/2003

Section I

Manufacturer's Name: QUEST CHEMICAL CORPORATION	Telephone Numbers:
Address: 12255 FM 529	Emergency:
NORTHWOODS INDUSTRIAL PARK	800/255-3924
HOUSTON	Information:
State: TX Zip Code: 77041	713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
AROMATIC PET. DISTILLATES	64742-94-5	NOT EST.	NOT EST.		_____
ISOPROPYL ALCOHOL	67-63-0	400 PPM	400 PPM	N/A	_____
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	350F+	Specific Gravity (water=1)	0.89
Vapor Pressure(mm Hg)	<5	Melting Point:	N/A
Vapor Density(AIR=1)	4	Evaporation Rate:	<1
Solubility in Water:	0%	(Butyl Acetate=1)	

Appearance and Odor: BROWN COLORED SPRAY, PETROLEUM ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used):142F TCC Flammable Limits: LEL:1.0 UEL: 6.0
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS

Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatibility (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY
PRODUCE CARBON MONOXIDE.

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY LEAD TO UNCONSCIOUSNESS.
INGESTION: NAUSEA. SKIN: IRRITATION AND REDDENING. EYES: IRRITATION AND
REDDENING.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE
WILL AGGRAVATE RESPIRATORY.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. APPLY
ARTIFICIAL RESPIRATION IF INDICATED. INGESTION: DO NOT INDUCE VOMITING.
CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. EYES: FLUSH WITH
WATER FOR 15 MINUTES AND CALL PHYSICIAN. SKIN: WASH WITH SOAP AND WATER.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH
RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL GUIDELINES.

Precautions to be Taken in Handling and Storing: DO NOT PUNCTURE OR
INCINERATE CONTAINER. DO NOT REUSE EMPTY CONTAINER. WRAP CONTAINER AND
PLACE IN TRASH COLLECTION.

Other Precautions: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME. EXPOSURE
TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. VAPOR MAY COLLECT IN LOW
LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREAS.
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: RECOMMENDED
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USE.
Other Protective Clothing or Equipment: N/A
Work/Hygienic Practices: WASH HANDS AFTER USE.